

BECAUSE
IMPROVEMENT
NEVER
STOPS



AVSD 360-3600
REFRIGERANT DRYERS

AVSD: A REVOLUTION IN DRYER EFFICIENCY

The ALUP AVSD refrigerant dryers are making top quality air at previously unimaginable energy savings a reality. Their variable speed drive ensures that your dryer will only use the energy needed to match your compressed air demand. In addition to their unparalleled efficiency, they also deliver stable, high air purity and a small carbon footprint.

② UNMATCHED ENERGY SAVINGS

- Lower operational cost due to lower electricity bills and maintenance costs.
- Quick return on investment (ROI), as low as 1.5 year.

① HIGHER PRODUCTION QUALITY AND RELIABILITY

- Increase your operational reliability by safeguarding downstream equipment, such as piping, receiver and machinery.
- Boost your output thanks to higher uptime and process optimization results by connecting to your compressor room communication protocol.
- Advanced controller and ICONS remote connectivity give you production insights, flexibility, efficiency and reliability.

③ ENVIRONMENTALLY FRIENDLY

- Contribute to a CO₂-neutral production process and greener society.
- Achieve your environmental goals.
- GWP gas regulation compliant.

④ SMART, COMPACT DESIGN

- Small footprint to fit on your production floor or in your utility room.
- Easy to move and to access for service.



AVSD: STRENGTH IN NUMBERS

- Variable speed drive delivers up to **60% in energy savings**.
- Best in class microchannel refrigerant condenser **lowers gas charge** and therefore your carbon footprint.
- ISO 8573-1:2010 **air purity Class 4** guaranteed, even in high ambient (**46°C**) temperatures.
- **Up to 65% less CO₂ emissions** in TEWI (Total Equivalent Warming Impact) compared to fixed speed dryers, up to **55%** less than thermal mass dryers currently on the market.
- Up to **33% smaller size** than thermal mass dryers.
- Available in **several sizes** from **360 to 3600 m³/hr.**






EXCEPTIONAL DRYER PERFORMANCE & QUALITY AIR

IMPROVE YOUR OPERATIONAL RELIABILITY AND QUALITY

Installing an air dryer is the smart choice, as compressed air contains moisture that can damage your air system, your pneumatic equipment and your products. Unfortunately, not all refrigerant dryers give you reliable performance and air quality. With a guaranteed ISO 8573-1:2010 Class 4 air purity, the ALUP AVSD gives you protection and peace of mind. What is more, with the advanced Airlogic²T controller, you can monitor and control your AVSD to enhance its efficiency and reliability. And with an ICONS remote monitoring plan, you can optimize its operation even further.

VSD: REDUCE YOUR TOTAL COST OF OWNERSHIP

By matching its power usage to your air demand, the AVSD can decrease your dryer energy consumption by up to 60%. In addition, the new ALUP VSD dryer also delivers indirect savings: Its patented heat exchanger reduces the pressure drop and therefore results in even lower operating costs. By drastically lowering your total cost of dryer ownership on these two fronts, the AVSD offers you a return on investment as quick as 1.5 year.




ACHIEVE YOUR ENVIRONMENTAL GOALS


Sustainability is not a vague goal anymore; it has become a production KPI. The AVSD delivers a measurable contribution to your environmental and emission objectives with a low TEWI score (Total Equivalent Warming Impact). The dryer features the R513A refrigerant, which is GWP gas regulation compliant and has a zero-ozone depletion potential.

THE SUPERIOR ALTERNATIVE TO THERMAL MASS

For many years, the most efficient dryers were the so-called thermal mass dryers, which run at full load to cool a thermal mass, then stop and rely on that mass for cooling before repeating the process. However, this process is inefficient as the dryer still needs to run at full load to cool the thermal mass. In addition, thermal mass dryers offer limited or no energy savings in high ambient temperatures.

Compared to thermal mass technology, VSD dryers offer real innovation and vastly superior energy savings. It is also important to point out that the dew point of VSD dryers stays consistently low. The result: A constant supply of high-quality air. The dew point of thermal mass compressors, however, rises and falls, which compromises air quality by up to 2 purity classes.





ONE RELIABLE SOURCE FOR ALL YOUR COMPRESSED AIR NEEDS

ALUP stands ready to meet all of your compressed air needs: From the compressor ① itself and the new VSD dryer ② to line filters ③, oil-water separators ④, air receiver buffer storage ⑤, our own easy-to-install AIRnet piping system ⑥, and a central controller to manage the entire system ⑦. All of these products are available in the proven ALUP quality and each of them is built to last.

ICONS

INCREASED UPTIME, POWERED BY ICONS



Are you keeping an eye on your dryer's running parameters and service alerts? With an Intelligent CONNectivity System (ICONS), you get data and insights from your Airlogic²T controller delivered to your computer, tablet or smartphone. The result: no surprise breakdowns, no unforeseen costs:

- On-time maintenance to control costs and ensure a longer machine life.
- Potential problems are recognized before they can pose a threat to the continuity of your production.

What is more, ICONS allows for truly proactive compressor and production management and optimization, with analyses and reports indicating potential energy savings and other enhancements.




A CLOSER LOOK AT THE AVSD

REFRIGERANT COMPRESSOR WITH VSD INVERTER:

Matches its speed to your air demand to save on energy use and costs.

HIGH-EFFICIENCY HEAT EXCHANGER:

Patented design with air-to-air side to reduce pressure drop.



ZERO-LOSS DRAIN:

Features a level sensor to open the drain only when needed to prevent unnecessary loss of compressed air.

SINGLE ELECTRICAL CONNECTION:

Ensures quick and easy installation.


AIRLOGIC²T CONTROLLER: with warning indications, dryer shutdown and maintenance scheduling. Also comes with ICONS remote monitoring to maximize your dryer performance and energy efficiency.



BETTER FOR THE ENVIRONMENT: A GOOD TEWI SCORE

The AVSD produces 65% less CO₂ emissions calculated in TEWI compared to fixed speed dryers, up to 55% less than thermal mass dryers currently on the market. But what does this TEWI score mean?

TEWI, short for Total Equivalent Warming Impact, is a measure that reflects the global warming impact of refrigerant equipment based on the emissions of greenhouse gases during the life-time of the equipment and the disposal of the operating fluids at the end. TEWI takes into account direct refrigerant emissions as well as and indirect emissions produced through the energy consumed in operating the equipment.



$$\text{TEWI} = \text{GWP (direct; refrigerant leaks and recovery/recycling)} + \text{GWP (indirect; operation)}$$

$$= (\text{GWP} \times \text{L}_{\text{annual}} \times \text{n}) + \text{GWP} \times \text{m} \times (1 - \alpha_{\text{recovery}}) + (\text{E}_{\text{annual}} \times \beta \times \text{n})$$

Where:

GWP = Global Warming Potential of refrigerant, relative to CO₂ (GWP CO₂ = 1)

L_{annual} = Leakage rate per year (Units: kg)

n = System operating life (Units: years)

m = Refrigerant charge (Units: kg)

α_{recovery} = Recovery/recycling factor from 0 to 1

E_{annual} = Energy consumption per year (Units: kWh p.a.)

β = Indirect emission factor (Units: kg CO₂ per kWh)


TECHNICAL SPECIFICATIONS AVSD

Model	Inlet flow for pressure dew point (PDP) of 3°C/37.4°F			Pressure drop at full flow		Power consumption		Max. working pressure		Compressed air connections (NPT for UL version)	Dimensions						Weight	
	l/s	cfm	m³/hr	bar	psi	kW	hp	bar	psi		B mm	B in	A mm	A in	C mm	C in	kg	lb
AVSD 360	100	212	360	0.16	2.3	0.66	0.90	14.5	210	G 1 ½" F	805	31.69	1069	42.09	962	37.87	130	287
AVSD 500	140	297	500	0.11	1.6	1.04	1.41	14.5	210	G 2" F	805	31.69	1069	42.09	962	37.87	134	295
AVSD 650	180	381	650	0.18	2.6	1.54	2.09	14.5	210	G 2" F	805	31.69	1069	42.09	962	37.87	134	295
AVSD 790	220	466	790	0.14	2	1.77	2.41	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	143	315
AVSD 940	260	551	940	0.1	1.5	1.9	2.58	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	150	331
AVSD 1080	300	636	1080	0.18	2.6	2.64	3.59	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	165	364

LOW GWP DRYER WITH R513A

Model	Inlet flow for pressure dew point (PDP) of 3°C/37.4°F			Pressure drop at full flow		Power consumption		Max. working pressure		Compressed air connections (NPT for UL version)	Dimensions						Weight	
	l/s	cfm	m³/hr	bar	psi	kW	hp	bar	psi		B mm	B in	A mm	A in	C mm	C in	kg	lb
AVSD 790 G	220	466	790	0.14	2	1.92	2.57	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	174	384
AVSD 940 G	260	551	940	0.1	1.5	2.63	3.53	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	180	397
AVSD 1080 G	300	636	1080	0.18	2.6	3.36	4.50	14.5	210	G 2 1/2" F	805	31.69	1069	42.09	962	37.87	180	397
AVSD 1295	360	763	1296	0.20	2.9	2.52	3.38	14	203	3" M	1132	44.56	1012	39.82	1399	55.08	235	518
AVSD 1655	460	975	1656	0.20	2.9	2.61	3.50	14	203	3" M	1121	44.13	1012	39.82	1596	62.83	330	728
AVSD 1910	530	1123	1908	0.20	2.9	3.00	4.02	14	203	3" M	1121	44.13	1012	39.82	1596	62.83	345	761
AVSD 2375	660	1398	2376	0.20	2.9	4.55	6.10	14	203	DN 100	1121	44.13	1012	39.82	1826	71.89	405	893
AVSD 3170	880	1865	3168	0.20	2.9	5.43	7.28	14	203	DN 100	1531	60.27	1012	39.82	1826	71.89	505	1113
AVSD 3600	1000	2119	3600	0.20	2.9	5.76	7.72	14	203	DN 100	1531	60.27	1012	39.82	1826	71.89	505	1113

Data refers to 50Hz air-cooled version.



REFERENCE CONDITIONS:

Ambient temperature: 25°C
 Compressed air inlet temperature: 35°C
 Working pressure: 7 bar (g)

LIMITATIONS:

(Operating limit conditions for AVSD 360 - 1080)

Max. ambient temp: 46°C
 Min. ambient temp: 5°C
 Max. air inlet temp: 60°C
 Max. compressed air inlet pressure: 14.5 bar (g)


(Operating limit conditions for AVSD 1295 - 3600)

Max. ambient temp: 46°C
 Min. ambient temp: 5°C
 Max. air inlet temp: 60°C
 Max. compressed air inlet pressure: 14 bar (g)

NOTES:

Refrigerant type: R410A (Model: AVSD 360 - 1080)
 R513A (Model: AVSD 790 G / 940 G / 1080 G)
 R513A (Model: AVSD 1295 - 3600)

ALUP'S HERITAGE



Founded in Germany in 1923, ALUP derives its name from the automotive products that were manufactured in the mechanical workshop in Köngen where the company came into existence: Auto-Luft-Pumpen. ALUP developed its first piston compressor just two years later. In 1980, rotary screw compressors were added to its product range.

The experience and expertise the company gained each year, coupled with a spirit of innovation, has led to today's high-quality product offer. The name ALUP Kompressoren has become synonymous with innovative technology blended with a strong sense of tradition. To this day, ALUP Kompressoren is operating out of the heart of Baden-Württemberg, where it all began nearly a century ago.

DRIVEN BY TECHNOLOGY, DESIGNED BY EXPERIENCE

Discover what happens when passion for technology meets hands-on industrial experience: Designs that are easier to install and maintain, allowing you to focus on your job. Our extensive product range features the right machine for you – including the options that meet your performance requirements perfectly. High energy efficiency ensures return on investment and reduces your carbon footprint. And, because customer proximity is one of our hallmarks, you will always be one step ahead when your needs change.



1923 1925

Founded in
Germany

First piston
compressor

1980

First rotary
screw compressors

today

Innovative technology





Contact your local ALUP Kompressoren representative



Care

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

Trust

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

Efficiency

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.



www.alup.com

ALUP
Kompressoren